JANOLI International Journal of
Mathematical Sciences
(A Peer Review Journal)

journal homepage: https://janolijournals.com/index.php/jijms

Volume 2, Issue 1, 2026 ISSN(online):3107-443X

Mathematical Formulation on Fluid and Heat Transfer in Various Types of Channels

Vikash Rai, Raubin Kumar, and D. Gautam
Department of Mathematics, Madhyanchal Professional University, Bhopal, Madhya Pradesh, India

ARTICLE INFO

Article History:
Received March 7 , 2026
Revised March 7, 2026
Accepted March 7, 2026
Available online March 22, 2026

Keywords:

Fluid flow, Heat transfer, Channel flow, Navier–Stokes equations, Convection, Microchannels, Porous media, Mathematical modeling.

Correspondence:

E-mail:
vikashjiorai@gmail.com

ABSTRACT

Fluid flow and heat transfer in channels constitute a fundamental area of research in mechanical, chemical, civil, and biomedical engineering. Mathematical modeling of transport phenomena in channels of different geometries—such as parallel plate channels, circular pipes, microchannels, and porous channels—provides critical insights into velocity distribution, temperature profiles, pressure drop, and thermal performance. This paper presents a comprehensive mathematical formulation governing fluid flow and heat transfer in various types of channels under laminar and turbulent conditions. The derivation is based on the conservation laws of mass, momentum, and energy, leading to the Navier–Stokes and energy equations. Dimensionless analysis using Reynolds, Prandtl, and Nusselt numbers is discussed to characterize flow regimes and thermal behavior. Special cases including fully developed flow, forced convection, and conjugate heat transfer are analyzed. The study highlights the impact of channel geometry, boundary conditions, and fluid properties on transport characteristics and provides a unified framework for further theoretical and computational investigations.

1. Introduction

Fluid and heat transfer in channels play a vital role in applications such as heat exchangers, microfluidic devices, cooling systems, biomedical transport, and chemical reactors. The accurate mathematical modeling of these phenomena enables engineers to optimize system performance and predict operational behavior under different physical conditions.

The governing equations for fluid flow are derived from the conservation principles of mass, momentum, and energy. The fundamental equations describing Newtonian fluid motion are the Navier–Stokes equations, formulated by Claude-Louis Navier and later refined by George Gabriel Stokes. These equations, coupled with the energy equation, provide the mathematical basis for analyzing convection and conduction heat transfer in channels.

Channel geometry significantly influences flow characteristics. Common configurations include:

- ✓ Parallel plate channels
- ✓ Circular pipes
- ✓ Rectangular ducts
- ✓ Annular channels

✓ Microchannels
✓ Porous channels

Understanding the transport mechanisms in these geometries is essential for both theoretical and practical advancements.

2. Literature Review

The study of fluid flow and heat transfer in channels has evolved from classical analytical solutions to sophisticated numerical and experimental investigations encompassing complex fluids, geometries, and multiphysics effects.

2.1 Classical Analytical Developments

Early theoretical developments focused on fully developed laminar flow in simple geometries such as circular pipes and parallel plate channels. The Hagen–Poiseuille solution established the parabolic velocity profile for viscous flow under a constant pressure gradient. Subsequent analytical solutions extended to non-circular ducts using separation of variables and eigenfunction expansions.

The Graetz problem further examined thermal entrance effects in laminar pipe flow, introducing the concept of thermal development length. These classical solutions formed the basis for defining Nusselt numbers under constant wall temperature and constant heat flux conditions.

2.2 Turbulent Channel Flow

Turbulent flow in channels received extensive attention due to its practical importance in engineering systems. Semi-empirical approaches such as Prandtl's mixing-length theory and logarithmic velocity distribution were foundational in turbulent modeling.

Experimental studies of fully developed turbulent flow in smooth pipes led to friction factor correlations, notably the Blasius and Colebrook relations. Heat transfer correlations such as the Dittus–Boelter and Gnielinski equations became standard tools for predicting convective heat transfer coefficients.

Direct numerical simulations (DNS) and large eddy simulations (LES) significantly advanced understanding of turbulence structures in channel flow. High-resolution simulations revealed coherent structures such as streaks and vortices that influence heat transfer enhancement.

2.3 Convective Heat Transfer in Ducts

Comprehensive treatments of forced convection in ducts were provided by R. K. Shah and A. L. London, who compiled analytical and experimental results for various duct geometries in laminar regimes. Their work systematically categorized Nusselt number solutions for rectangular, triangular, and annular channels.

The contributions of Adrian Bejan emphasized entropy generation minimization and thermodynamic optimization in channel flows, leading to constructal design principles for enhanced heat transfer.

2.4 Microchannel and Minichannel Flows

With the development of microelectromechanical systems (MEMS), microchannel heat transfer emerged as a critical research field. Investigations demonstrated deviations from classical macroscale correlations due to:

- ✓ High surface-to-volume ratio
- ✓ Entrance effects dominance
- ✓ Slip flow regimes (for higher Knudsen numbers)
- ✓ Temperature-dependent fluid properties

Pioneering microchannel heat sink studies showed substantial heat removal capabilities for electronic cooling applications. Researchers also examined two-phase flow boiling in microchannels, observing flow instabilities and pressure oscillations not commonly present in macroscale systems.

2.5 Non-Newtonian Fluid Flow in Channels

Many industrial fluids exhibit non-Newtonian behavior. Power-law, Bingham plastic, Casson, and Carreau models have been incorporated into channel flow formulations. Analytical and numerical studies reveal significant changes in velocity distribution and pressure drop compared to Newtonian fluids.

Heat transfer in non-Newtonian channel flows has been studied under constant wall temperature and heat flux conditions. Results indicate that shear-thinning fluids often enhance heat transfer due to thinner thermal boundary layers.

2.6 Magnetohydrodynamic (MHD) Channel Flow

Magnetohydrodynamic flow in channels has applications in metallurgy, cooling of nuclear reactors, and MHD generators. When an external magnetic field is applied perpendicular to the flow, Lorentz forces modify the momentum equation. The Hartmann number characterizes magnetic influence.

Analytical solutions for Hartmann flow between parallel plates demonstrate that increasing magnetic field strength suppresses velocity fluctuations and thickens the velocity boundary layer, affecting heat transfer rates.

2.7 Porous Channel and Brinkman Models

Flow in porous channels has been widely investigated using Darcy’s law and its extensions. The Brinkman–Forchheimer model accounts for viscous shear and inertial effects. Studies show that permeability significantly affects pressure drop and heat transfer.

Conjugate heat transfer problems in porous-filled channels are relevant for compact heat exchangers and geothermal systems. Thermal dispersion effects are often included in advanced models.

2.8 Nanofluids and Enhanced Heat Transfer

Recent research explores nanofluids—base fluids containing nanoparticles—to improve thermal conductivity. Experimental results report enhanced Nusselt numbers in channel flows, though debates continue regarding stability and pumping power penalties.

Mathematical models incorporate modified effective thermal conductivity and viscosity correlations. Both single-phase and two-phase models have been proposed to describe nanoparticle transport mechanisms such as Brownian motion and thermophoresis.

2.9 Numerical and Computational Developments

The advancement of computational fluid dynamics (CFD) has revolutionized channel flow studies. Finite volume methods, widely implemented in commercial solvers, allow simulation of:

- ✓ Complex geometries
- ✓ Turbulent flows with RANS models (k–ε, k–ω)
- ✓ Multiphase flows
- ✓ Conjugate heat transfer

Benchmark DNS studies of turbulent channel flow have provided reference datasets for validating turbulence models.

2.10 Current Research Trends

Contemporary research focuses on:

- ✓ Machine learning-assisted turbulence modeling
- ✓ Topology optimization of channel networks
- ✓ Slip and rarefaction effects in nanoscale channels
- ✓ Bio-inspired microchannel cooling systems
- ✓ Entropy-based thermal performance evaluation

The integration of experimental, analytical, and numerical approaches continues to expand the understanding of transport phenomena in channels.

3. Computational Approaches for Channel Flow and Heat Transfer

Analytical solutions of the Navier–Stokes and energy equations are limited to simplified geometries and ideal boundary conditions (e.g., fully developed laminar flow, constant properties, simple cross-sections). However, practical engineering systems often involve:

- ✓ Complex geometries (corrugated, wavy, ribbed channels)

✓ Turbulent or transitional flows

✓ Conjugate heat transfer

✓ Variable thermophysical properties

✓ Multiphase or non-Newtonian fluids

In such cases, computational fluid dynamics (CFD) techniques are employed. The most widely used numerical methods include:

3.1. Finite Difference Method (FDM)

The Finite Difference Method replaces differential operators with algebraic difference approximations using Taylor series expansions. For example:

$$\frac{\partial^2 u}{\partial y^2} \approx \frac{u_{i+1} - 2u_i + u_{i-1}}{\Delta y^2}$$

FDM is particularly efficient for structured grids and simple geometries such as parallel plate channels and rectangular ducts. It has been extensively used for:

✓ Solving developing flow problems

✓ Studying transient heat conduction

✓ Analyzing stability in channel flows

However, FDM is less flexible for irregular geometries.

3. 2. Finite Volume Method (FVM)

The Finite Volume Method integrates governing equations over discrete control volumes:

$$\int_{CV} \nabla \cdot (\rho \mathbf{V}) dV = 0$$

Using Gauss divergence theorem, volume integrals are converted into surface fluxes. FVM ensures conservation of mass, momentum, and energy at the discrete level, making it highly suitable for fluid flow simulations.

It is widely implemented in commercial CFD solvers and used for:

✓ Turbulent channel flow (RANS, LES models)
✓ Multiphase flow in microchannels
✓ Conjugate heat transfer problems

✓ Porous media transport

3.3. Finite Element Method (FEM)

The Finite Element Method approximates variables using interpolation (shape) functions:

$$u(x,y) \approx \sum_{j=1}^{n} N_j(x,y) u_j$$

FEM is particularly powerful for:

✓ Complex geometries
✓ Irregular boundaries
✓ Coupled Multiphysics problems (fluid–structure interaction)
✓ Porous channel modelling

Weak formulations derived from weighted residual methods improve numerical stability and accuracy.

3.4. Turbulence Modelling

For turbulent channel flows, the instantaneous velocity is decomposed:

$u = \bar{u} + u'$

Reynolds-averaged Navier–Stokes (RANS) equations introduce Reynolds stresses requiring closure models such as:

✓ k–ε model
✓ k–ω model
✓ Reynolds Stress Model (RSM)

Large Eddy Simulation (LES) resolves large-scale eddies while modeling small scales, and Direct Numerical Simulation (DNS) resolves all scales but requires high computational cost.

4. Mathematical Formulation

4.1 Governing Equations

The behavior of fluid flow and heat transfer in channels is governed by the fundamental conservation laws of **mass, momentum, and energy**. For an incompressible Newtonian fluid with constant properties, the governing equations are as follows:

4.1.1 Continuity Equation (Conservation of Mass)

For incompressible flow, density remains constant. The continuity equation reduces to:

$$\nabla \cdot V = 0$$

where: V=(u,v,w) is the velocity vector

This equation ensures that the net mass flux entering a control volume equals the net mass flux leaving it.

4.1.2 Momentum Equation (Navier–Stokes Equation)

The momentum conservation equation for an incompressible Newtonian fluid is:

$$\rho\left(\frac{\partial \mathbf{V}}{\partial t} + \mathbf{V}\cdot\nabla\mathbf{V}\right) = -\nabla p + \mu\nabla^2\mathbf{V} + \mathbf{F}$$

where:

ρ= fluid density

μ= dynamic viscosity

p = pressure

F = body force per unit volume (e.g., gravity)

Physical interpretation:

$\rho\partial V/\partial t \rightarrow$ unsteady (local) acceleration

$\rho(V\cdot\nabla V) \rightarrow$ convective acceleration

$-\nabla p \rightarrow$ pressure gradient force

$\mu\nabla^2 V \rightarrow$ viscous diffusion

$F \rightarrow$ external body forces

For steady, fully developed, one-dimensional channel flow, this equation simplifies significantly.

4.1.3 Energy Equation (Conservation of Energy)

The thermal energy equation for incompressible flow with constant properties is:

$$\rho c_p\left(\frac{\partial T}{\partial t} + \mathbf{V}\cdot\nabla T\right) = k\nabla^2 T + \Phi$$

where: T = temperature

ρc_p = specific heat at constant pressure

k = thermal conductivity

Φ = viscous dissipation term

The viscous dissipation term becomes important in high-viscosity fluids or micro-scale flows.

5. Flow in Different Types of Channels

5.1 Parallel Plate Channel

Consider steady, fully developed laminar flow between two infinite parallel plates separated by a distance 2h.

Assumptions:

✓ Steady flow

✓ Fully developed (∂u/∂x=0)

✓ One-dimensional velocity: u=u(y)

✓ No-slip at walls

The simplified momentum equation becomes:

$$\mu \frac{d^2u}{dy^2} = \frac{dp}{dx}$$

Integrating twice and applying boundary conditions:

u(±h)=0

Velocity Profile:

$$u(y) = \frac{1}{2\mu}\left(-\frac{dp}{dx}\right)(h^2 - y^2)$$

This is a **parabolic profile** with:

✓ Maximum velocity at centerline (y=0)

✓ Zero velocity at walls (no-slip condition)

Maximum Velocity:

$$u_{max} = \frac{h^2}{2\mu}\left(-\frac{dp}{dx}\right)$$

Average Velocity:

$$U = \frac{2}{3} u_{max}$$

Heat Transfer Considerations:

Thermal analysis depends on boundary conditions:

✓ Constant wall temperature

✓ Constant wall heat flux

Each condition leads to different temperature distributions and Nusselt numbers.

5.2 Circular Pipe (Hagen–Poiseuille Flow)

For axisymmetric laminar flow inside a circular pipe of radius RRR, the governing equation reduces to:

$$\frac{1}{r}\frac{d}{dr}\left(r\frac{du}{dr}\right) = \frac{1}{\mu}\frac{dp}{dx}$$ Applying:

✓ Finite velocity at r=0

✓ No-slip at wall: u(R)=0

Velocity Profile:

$$u(r) = \frac{1}{4\mu}\left(-\frac{dp}{dx}\right)(R^2 - r^2)$$

Again, a **parabolic distribution**.

Maximum Velocity:

$$u_{max} = \frac{R^2}{4\mu}\left(-\frac{dp}{dx}\right)$$

Average Velocity:

$$U = \frac{R^2}{8\mu}\left(-\frac{dp}{dx}\right)$$

Thus:

$$u_{max} = 2U$$

This classical solution is known as **Hagen–Poiseuille flow**.

5.3 Rectangular Channel

For a rectangular duct with width aaa and height bbb, the velocity satisfies:

$$\frac{\partial^2 u}{\partial x^2} + \frac{\partial^2 u}{\partial y^2} = \frac{1}{\mu}\frac{dp}{dx}$$

This is a two-dimensional Poisson equation.

Solution Method:

✓ Separation of variables

✓ Fourier series expansion

The velocity profile is not purely parabolic; it depends on the aspect ratio. .

As the aspect ratio increases (wide duct), the solution approaches the parallel plate case.

5.4 Microchannels

When channel dimensions are very small (micron scale), rarefaction effects may appear.

The no-slip boundary condition may no longer hold. Instead, slip boundary condition is applied:

$$u_{wall} = L_s \left(\frac{\partial u}{\partial n}\right)$$

where: L_s = slip length

$\partial u/\partial n$ = velocity gradient normal to wall

Slip increases flow rate compared to classical no-slip predictions.

Microchannel flows are important in:

Lab-on-chip devices

MEMS systems

Biomedical diagnostics

5.5 Porous Channels

Flow in porous media is governed by **Darcy's Law**:

$$\mathbf{V} = -\frac{K}{\mu}\nabla p$$ where:

K = permeability

For higher velocity or transitional regimes, the **Brinkman equation** adds viscous diffusion:

$$\mu_{eff}\nabla^2\mathbf{V} - \frac{\mu}{K}\mathbf{V} = \nabla p$$

Porous channel flow is significant in:

✓ Filtration systems

✓ Packed-bed reactors

✓ Groundwater transport

6. Dimensionless Analysis

Dimensionless parameters help generalize results across geometries and scales.

6.1 Reynolds Number

$$Re = \frac{\rho U D_h}{\mu}$$

Determines flow regime:

Re<2300 → Laminar & Re>4000 → Turbulent

6.2 Prandtl Number

$$Pr = \frac{\mu c_p}{k}$$

Represents ratio of momentum diffusivity to thermal diffusivity.

6.3 Nusselt Number

$$Nu = \frac{hD_h}{k}$$

Measures convective heat transfer relative to conduction.

7. Boundary Conditions

7.1 Hydrodynamic Boundary Conditions

✓ No-slip condition (classical flows)

✓ Slip condition (microchannels)

✓ Symmetry condition at the centerline

7.2 Thermal Boundary Conditions

- Constant wall temperature
- Constant wall heat flux
- Convective boundary condition
- Each produces different thermal field solutions.

8. Applications

✓ The mathematical formulation applies to numerous engineering systems:

✓ Heat exchangers

✓ Microfluidic chips

✓ Nuclear reactor cooling systems

✓ Biomedical flows (blood flow modeling)

✓ Solar thermal collectors

9. Conclusion

A unified mathematical framework based on conservation principles has been presented for fluid flow and heat transfer in different channel geometries. Analytical solutions for parallel plates, circular pipes, and rectangular ducts demonstrate how geometry strongly influences velocity distribution and heat transfer characteristics. Dimensionless analysis using Reynolds, Prandtl, and Nusselt numbers enables generalization across different systems.

Future work may include:

- ✓ Non-Newtonian fluid modeling
- ✓ Nanofluids
- ✓ Turbulence modeling
- ✓ Transient numerical simulations
- ✓ Multiphase flow analysis

This formulation provides a solid theoretical foundation for advanced computational and experimental investigations in fluid mechanics and thermal sciences.

References

1. Bird, R. B., Stewart, W. E., & Lightfoot, E. N. (2002). *Transport Phenomena* (2nd ed.). John Wiley & Sons.
2. Incropera, F. P., DeWitt, D. P., Bergman, T. L., & Lavine, A. S. (2007). *Fundamentals of Heat and Mass Transfer* (6th ed.). John Wiley & Sons.
3. White, F. M. (2011). *Fluid Mechanics* (7th ed.). McGraw-Hill Education.
4. Kays, W. M., Crawford, M. E., & Weigand, B. (2005). *Convective Heat and Mass Transfer* (4th ed.). McGraw-Hill.
5. Adrian Bejan (2013). *Convection Heat Transfer* (4th ed.). John Wiley & Sons.
6. R. K. Shah & A. L. London (1978). *Laminar Flow Forced Convection in Ducts*. Academic Press.
7. Vafai, K. (Ed.). (2005). *Handbook of Porous Media* (2nd ed.). CRC Press.
8. Kandlikar, S. G., Garimella, S., Li, D., Colin, S., & King, M. R. (2014). *Heat Transfer and Fluid Flow in Minichannels and Microchannels* (2nd ed.). Elsevier.
9. Yarin, L. P., Mosyak, A., & Hetsroni, G. (2009). *Fluid Flow, Heat Transfer and Boiling in Micro-Channels*. Springer.
10. Mortensen, N. A., Okkels, F., & Bruus, H. (2005). Shape dependence of hydraulic resistance in microchannels. *Physical Review E*, 71(5), 057301.
11. Kumar,N. and Kumar,S. (2005). A Computational Study of Oxygen Transport in the Body of Living Organism. *International Journal of Engineering*, *18*(4), 351-358.
12. Rajput,R. K. S. , Pant,A. and Kumar,N. (2009). Elastico-Viscous Flow between Two Rotating Discs of Different Transpiration for High Reynolds Numbers (RESEARCH NOTE). *International Journal of Engineering*, *22*(2), 115-122.

13. Kumar,N. (2011). A Computational Study of Metabolism in Sprinting (TECHNICAL NOTE). *International Journal of Engineering*, *24*(1), 75-80.

14. Baloni,J. , Rana,U. and Kumar,N. (2009). Mathematical Modeling for Homogeneous Tumor with Delay in Time. *International Journal of Engineering*, *22*(1), 49-56.